



# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** 366  
**Product name** 66c Spray Adhesive  
**Effective date** 13-Nov-2007  
**Company information** Sprayway, Inc.  
1005 Westgate Drive  
Addison, IL 60101 United States  
**Company phone** General Assistance 1-630-628-3000  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Supersedes date** 01-May-2007

## 2. Hazards Identification

**Emergency overview** EXTREMELY FLAMMABLE  
CONTENTS UNDER PRESSURE.  
Aerosol. Pressurized container may explode when exposed to heat or flame.

**OSHA regulatory status** Irritating to eyes. Prolonged exposure may cause chronic effects.  
This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

**Potential health effects**

**Eyes** Causes eye irritation.

**Skin** Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

**Target organs** Central nervous system. Respiratory system.

**Chronic effects** May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.

**Signs and symptoms** Discomfort in the chest. Narcosis. Defatting of the skin. Irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
Methyl Acetate	79-20-9	20 - 30
Heptane	142-82-5	20 - 30
Dimethyl Ether	115-10-6	15 - 20
Isobutane	75-28-5	10 - 15
Propane	74-98-6	5 - 8
Non-hazardous and other components below reportable levels		10 - 20

## 4. First Aid Measures

### First aid procedures

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.

**Skin contact** Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Ingestion**

Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**Notes to physician**

Symptoms may be delayed.

**General advice**

Call a physician if symptoms develop or persist.

**5. Fire Fighting Measures****Flammable properties**

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back.

**Extinguishing media****Suitable extinguishing media**

Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Do not use water.

**Unsuitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire. Water may be ineffective.

**Protection of firefighters****Specific hazards arising from the chemical**

Fire may produce irritating, corrosive and/or toxic gases.

**Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**Specific hazards**

Fire may produce irritating, corrosive and/or toxic gases.

**6. Accidental Release Measures****Personal precautions**

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away.

**Methods for containment**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

**Methods for cleaning up**

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

**7. Handling and Storage****Handling**

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

**Storage**

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children. Use care in handling/storage.

**8. Exposure Controls / Personal Protection****Exposure limits****ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Methyl Acetate

79-20-9

200 ppm

250 ppm

Not established

Heptane

142-82-5

400 ppm

500 ppm

Not established

Isobutane

75-28-5

1000 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

**OSHA****Components****CAS #****TWA****STEL****Ceiling**

Methyl Acetate

79-20-9

200 ppm

Not established

Not established

Heptane

142-82-5

500 ppm

Not established

Not established

Propane

74-98-6

1000 ppm

Not established

Not established

**Engineering controls**

Ensure adequate ventilation, especially in confined areas.

**Personal protective equipment****Eye / face protection**

Wear chemical goggles.

**Skin protection**

Wear appropriate chemical resistant gloves.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**General hygiene considerations**

When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Handle in accordance with good industrial hygiene and safety practice.

**9. Physical & Chemical Properties****Appearance**

Compressed liquefied gas.

**Color**

Tan.

**Odor**

Solvent.

**Physical state**

Liquid.

**Form**

Aerosol.

**Flammability (HOC)**

31.29 kJ/g estimated

**Flash back**

Yes

**Pressure**

37 - 47 psig @ 70F

**Solubility**

Partially

**Flash point**

-156 °F (-104.4 °C) estimated

**Boiling point**

37.4 °F (2.8 °C) estimated

**Specific gravity**

0.7276

**pH**

Not applicable

**10. Chemical Stability & Reactivity Information****Chemical stability**

Risk of ignition.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

This product is incompatible with nitrates.

**Hazardous decomposition products**

May include oxides of nitrogen.

**11. Toxicological Information****Acute effects**Acute LD50: 18897 mg/kg estimated, Rat, Oral  
Acute LD50: 18897 mg/kg estimated, Rat, Dermal  
Acute LC50: 4249 mg/l/4h estimated, Rat, Inhalation**Sensitization**

Not expected to be hazardous by OSHA criteria.

**Local effects**

Irritating to eyes. Components of the product may be absorbed into the body through the skin.

**Chronic effects**

Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects.

**Neurological effects**

Hazardous by OSHA criteria.

**Mutagenicity**

Not expected to be hazardous by OSHA criteria.

**Reproductive effects**

Not expected to be hazardous by OSHA criteria.

**Teratogenicity**

Not expected to be hazardous by OSHA criteria.

**Epidemiology**

Hazardous by OSHA criteria.

**Further information**

Symptoms may be delayed.

## 12. Ecological Information

**Ecotoxicity** LC50 713 mg/L estimated, Fish, 96.00 Hours,  
EC50 3882 mg/L estimated, Daphnia, 48.00 Hours,  
IC50 457 mg/L estimated, Algae, 72.00 Hours,  
Components of this product have been identified as having potential environmental concerns.

## 13. Disposal Considerations

**Waste codes** D001: Waste Flammable material with a flash point <140 F  
**Disposal instructions** Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

**Proper shipping name** Consumer commodity  
**Hazard class** ORM-D  
**Subsidiary hazard class** None  
**Additional information:**  
**Packaging exceptions** 156, 306  
**Packaging non bulk** 156, 306  
**Packaging bulk** None

### IMDG

Not regulated as hazardous goods.

### IATA

Not regulated as hazardous goods.

## 15. Regulatory Information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

### Occupational Safety and Health Administration (OSHA)

**29 CFR 1910.1200 hazardous chemical** Yes

### CERCLA (Superfund) reportable quantity

None

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**Section 302 extremely hazardous substance** No

**Section 311 hazardous chemical** Yes

### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## State regulations

### U.S. - Pennsylvania - RTK (Right to Know) List

Dimethyl Ether	115-10-6	Present
Heptane	142-82-5	Present
Isobutane	75-28-5	Present
Methyl Acetate	79-20-9	Present
Propane	74-98-6	Present

## 16. Other Information

### HMIS® ratings

Health: 2\*  
Flammability: 4  
Physical hazard: 0

### Prepared by

Regulatory Compliance

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### Issue date

13-Nov-2007