

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 055

Product name Fast Tack Foam and Fabric Adhesive

Effective date 06-Jan-2009
Company information Sprayway, Inc. 484 Vista Ave.

Addison, IL 60101 United States

Company phone General Assistance 1-630-628-3000

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 05

Supersedes date 20-Feb-2008

2. Hazards Identification

Emergency overview FLAMMABLE

CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when

exposed to heat or flame.

Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Eyes Causes eye irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system. Respiratory system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Propane	74-98-6	15 - 20
Acetone	67-64-1	15 - 20
n-Butane	106-97-8	15 - 20
n-Hexane	110-54-3	10 - 15
Methyl Acetate	79-20-9	10 - 15
Cyclohexane	110-82-7	1 - 3
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition

sources and flash back.

Extinguishing media

Suitable extinguishing media

Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2). Halons. Do not use

water.

Protection of firefighters

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the

leak is irreparable.

Methods for cleaning up

Should not be released into the environment.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
n-Hexane	110-54-3	50 ppm	1000 ppm	Not established
Methyl Acetate	79-20-9	200 ppm	250 ppm	Not established
Cyclohexane	110-82-7	100 ppm	Not established	Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
n-Hexane	110-54-3	500 ppm	Not established	Not established
Methyl Acetate	79-20-9	200 ppm	Not established	Not established
Cyclohexane	110-82-7	300 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Wear chemical goggles. **Skin protection** Protective gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 51.8 °F (11.1 °C) estimated

Color Tan.

Flammability (HOC) 41.295 kJ/g estimated

Flash back No

Flash point -156 °F (-104.4 °C) estimated

Form Aerosol.

Odor Solvent.

PH Not applicable

Physical state Liquid.

Pressure 60 - 80 psig @ 70F

Solubility None

Sensitization

Specific gravity 0.7035 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.

Conditions to avoid Heat, flames and sparks.

Incompatible materialsThis product is incompatible with nitrates. **Hazardous decomposition products**May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects Acute LD50: 12805 mg/kg estimated, Rat, Dermal

Acute LC50: 272 mg/l/4h estimated, Rat, Inhalation Not expected to be hazardous by OSHA criteria.

Reproductive effectsNot expected to be hazardous by OSHA criteria. **Teratogenicity**Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 28.99 mg/L estimated, Fish, 96.00 Hours,

EC50 8435 mg/L estimated, Daphnia, 48.00 Hours, IC50 1092 mg/L estimated, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Do not allow this material to drain into sewers/water supplies. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose in

accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions156, 306Packaging non bulk156, 306Packaging bulkNone

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1UN number1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 UN number 1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Cyclohexane 110-82-7 1.0 % de minimis concentration n-Hexane 110-54-3 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000 n-Hexane: 5000.0000 Cyclohexane: 1000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone 67-64-1 Environmental hazard Cyclohexane 110-82-7 Environmental hazard Methyl Acetate 79-20-9 Present

 Methyl Acetate
 79-20-9
 Present

 n-Butane
 106-97-8
 Present

 n-Hexane
 110-54-3
 Present

 Propane
 74-98-6
 Present

16. Other Information

HMIS® ratings Health: 1*

Flammability: 4 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Hazards Identification: Emergency overview

Handling and Storage: Storage

Physical & Chemical Properties: Physical & Chemical Properties

Transport Information: Agency Name and Packaging Type/Transport Mode Selection