



MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 821-003
Product name **No Fray Spray**
Effective date 25-Jan-2010
Company information Sprayway, Inc.
484 Vista Ave.
Addison, IL 60101 United States
Company phone General Assistance 630-543-7600
Emergency telephone US 800-424-9300
Emergency telephone outside US 703-527-3887
Version # 09
Supersedes date 11-Dec-2009

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. Aerosol. Will be easily ignited by heat, spark or flames. Cancer hazard. Irritating to skin. Irritating to eyes. Irritating to respiratory system. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Skin contact. Ingestion. Inhalation.

Eyes Causes eye irritation.

Skin Irritating to skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

Target organs Kidney. Central nervous system. Liver. Lungs.

Chronic effects Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

Signs and symptoms Discomfort in the chest. Narcosis. Liver enlargement. Jaundice. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Trichloroethylene	79-01-6	20 - 30
Propane	74-98-6	10 - 15
VM&P Naphtha	8032-32-4	10 - 15
Acetone	67-64-1	10 - 15
n-Butane	106-97-8	10 - 15
Light Aliphatic Solvent Naphtha	64742-89-8	8 - 10
Odorless Mineral Spirits	64742-48-9	3 - 5
Xylene	1330-20-7	1 - 3
Ethyl Alcohol	64-17-5	0.1 - 0.5
Ethyl Benzene	100-41-4	0.1 - 0.5
Non-hazardous and other components below reportable levels		10 - 20

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops or persists. For minor skin contact, avoid spreading material on unaffected skin.
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Ingestion	If material is ingested, immediately contact a poison control center. Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Alcohol foam. Dry chemical. Carbon dioxide (CO ₂). Do not use water jet.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling	Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.
Storage	Level 2 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS #	TWA	STEL	Ceiling
Trichloroethylene	79-01-6	10 ppm	25 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
VM&P Naphtha	8032-32-4	300 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Xylene	1330-20-7	100 ppm	150 ppm	Not established
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
Ethyl Benzene	100-41-4	100 ppm	125 ppm	Not established

OSHA

Components	CAS #	TWA	STEL	Ceiling
Trichloroethylene	79-01-6	100 ppm	Not established	200 ppm
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Xylene	1330-20-7	100 ppm	Not established	Not established
Ethyl Alcohol	64-17-5	1000 ppm	Not established	Not established
Ethyl Benzene	100-41-4	100 ppm	Not established	Not established

Personal protective equipment

Eye / face protection

Wear chemical goggles.

Skin protection

Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	113 °F (45 °C) estimated
Color	Clear.
Flammability (HOC)	29.6273 kJ/g estimated
Flash back	Yes
Flash point	-156 °F (-104.4 °C) Propellant
Form	Aerosol.
Odor	Solvent.
pH	Not applicable
Physical state	Liquid.
Pressure	55 - 75 psig @ 70F
Solubility	Partially
Specific gravity	0.7831 estimated

10. Chemical Stability & Reactivity Information

Chemical stability	Risk of ignition.
Conditions to avoid	Heat, flames and sparks.
Hazardous decomposition products	Irritants. Toxic gas. May include oxides of nitrogen.

11. Toxicological Information

Acute effects	Acute LD50: 14075 mg/kg estimated, Rat, Dermal
---------------	--

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Acetone	67-64-1	Oral LD50 Rat 5800 mg/kg
Ethyl Alcohol	64-17-5	Oral LD50 Rat 7060 mg/kg
Ethyl Benzene	100-41-4	Inhalation LC50 Rat 17.2 mg/L 4 h; Oral LD50 Rat 3500 mg/kg; Dermal LD50 Rabbit 15354 mg/kg
Light Aliphatic Solvent Naphtha	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Odorless Mineral Spirits	64742-48-9	Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Trichloroethylene	79-01-6	Inhalation LC50 Rat 8000 ppm 4 h; Inhalation LC50 Rat 26300 ppm 1 h; Oral LD50 Rat 4290 mg/kg; Dermal LD50 Rabbit >20 g/kg
VM&P Naphtha	8032-32-4	Inhalation LC50 Rat 3400 ppm 4 h
Xylene	1330-20-7	Inhalation LC50 Rat 5000 ppm 4 h; Inhalation LC50 Rat 47635 mg/L 4 h; Oral LD50 Rat 4300 mg/kg; Dermal LD50 Rabbit >1700 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity Hazardous by OSHA criteria.

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol 64-17-5 Monograph 96 [in preparation] (in alcoholic beverages)

IARC - Group 2A (Probably Carcinogenic to Humans)

Trichloroethylene 79-01-6 Monograph 63 [1995]; Supplement 7 [1987]

IARC - Group 2B (Possibly Carcinogenic to Humans)

Ethyl Benzene 100-41-4 Monograph 77 [2000]

Reproductive effects Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Teratogenicity Not expected to be hazardous by OSHA criteria. Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

12. Ecological Information

Ecotoxicity Components of this product are hazardous to aquatic life.

LC50 151 mg/L, Fish, 96.00 Hours,
EC50 9.67 mg/L, Daphnia, 48.00 Hours,
IC50 2091 mg/L, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
D040: Waste Trichloroethylene

Disposal instructions Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D

Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306

Packaging non bulk 156, 306

Packaging bulk None

IMDG**Basic shipping requirements:**

Proper shipping name AEROSOLS
Hazard class 2.1
UN number 1950
Additional information:
Packaging exceptions NOT a LTD QTY
Item 5TF
Labels required 2.1+6.1

**IATA****Basic shipping requirements:**

Proper shipping name Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Hazard class 2.1
Subsidiary hazard class 6.1
UN number 1950
Additional information:
Packaging exceptions LTD QTY
Labels required 2.1, 6.1



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Ethyl Benzene	100-41-4	0.1 % de minimis concentration
Trichloroethylene	79-01-6	0.1 % de minimis concentration
Xylene	1330-20-7	1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

Trichloroethylene: 100.0000
 Acetone: 5000.0000
 Xylene: 100.0000
 Ethyl Benzene: 1000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone	67-64-1	Environmental hazard
Ethyl Alcohol	64-17-5	Present
Ethyl Benzene	100-41-4	Environmental hazard
Light Aliphatic Solvent Naphtha	64742-89-8	Present
n-Butane	106-97-8	Present
Odorless Mineral Spirits	64742-48-9	Present
Propane	74-98-6	Present
Trichloroethylene	79-01-6	Environmental hazard
VM&P Naphtha	8032-32-4	Present
Xylene	1330-20-7	Environmental hazard

16. Other Information**Further information**

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 2*

Flammability: 3

Physical hazard: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Prepared by

Regulatory Compliance