

## MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

Product number 990-002

Product name Auto Care Vinyl Leather Cleaner

Effective date 19-Oct-2009
Company information Sprayway, Inc. 484 Vista Ave.

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 04

Supersedes date 24-Jul-2008

## 2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE. Aerosol.

Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

Potential health effects

**Routes of exposure** Eye contact. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin This product may be harmful if it is absorbed through the skin. Prolonged or repeated

contact can result in defatting and drying of the skin which may result in skin irritation and

dermatitis (rash).

InhalationIntentional misuse by concentrating and inhaling the product can be harmful or fatal.IngestionExposure by ingestion of an aerosol is unlikely. Components of the product may be

absorbed into the body by ingestion.

Target organs 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is

repeated and prolonged and may cause blood damage. These effects have not been

observed in humans.

Blood. Central nervous system.

Chronic effects Unconsciousness. Conjunctiva. May cause central nervous system disorder (e.g.,

narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and

blurred vision) and/or damage.

Signs and symptoms Corneal damage. Narcosis. Cyanosis. Conjunctivitis. Defatting of the skin. Irritation.

# 3. Composition / Information on Ingredients

Components	CAS#	Percent
2-Butoxyethanol	111-76-2	3 - 5
n-Butane	106-97-8	1 - 3
Non-hazardous and other components below reportable levels		> 90

## 4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

**Inhalation** If symptoms develop move victim to fresh air. If symptoms persist, get medical attention.

**Ingestion** Have victim rinse mouth thoroughly with water. If ingestion of a large amount does occur,

call a poison control center immediately.

trade\_name MSDS US

## 5. Fire Fighting Measures

Flammable properties

Extinguishing media

Vapor or gas may spread to distant ignition sources and flash back.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Protection of firefighters

Protective equipment and precautions for firefighters

Suitable extinguishing media

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up.

#### 6. Accidental Release Measures

**Methods for containment** 

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

## 7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

Storage

Level 1 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep the container dry. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

#### 8. Exposure Controls / Personal Protection

#### **Exposure limits**

**ACGIH** 

Components	CAS#	TWA	STEL	Ceiling
2-Butoxyethanol	111-76-2	20 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling
2-Butoxvethanol	111-76-2	50 ppm	Not established	Not established

#### Personal protective equipment

Eye / face protection Wear chemical goggles.

Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant Skin protection

clothina.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators. If permissible levels are exceeded use NIOSH

mechanical filter / organic vapor cartridge or an air-supplied respirator.

## 9. Physical & Chemical Properties

**Appearance** Aerosol.

210.2 °F (98.9 °C) estimated **Boiling point** 

Color White.

Flammability (HOC) 3.4905 kJ/g estimated

trade\_name MSDS US Flash back No

Flash point -156 °F (-104.4 °C) Propellant

Form Aerosol.

Odor Characteristic.

pH 12.2 Physical state Liquid.

**Pressure** 60 - 80 psig @70°F

Solubility Partially Specific gravity 0.9775

## 10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.

**Conditions to avoid** Heat, flames and sparks.

Incompatible materials None known.

Hazardous decomposition products No hazardous decomposition products are known.

# 11. Toxicological Information

Acute effects Acute LD50: 4582 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

2-Butoxyethanol 111-76-2 Inhalation LC50 Rat 2.21 mg/L 4 h; Inhalation LC50 Rat 450 ppm 4 h; Oral LD50 Rat

470 mg/kg; Dermal LD50 Rat 2270 mg/kg; Dermal LD50 Rabbit 220 mg/kg

n-Butane 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Teratogenicity Not expected to be hazardous by OSHA criteria.

## 12. Ecological Information

**Ecotoxicity** Components of this product have been identified as having potential environmental

concerns.

LC50 1180 mg/L estimated, Fish, 96.00 Hours, EC50 43631 mg/L estimated, Daphnia, 48.00 Hours, IC50 89.14 mg/L estimated, Algae, 72.00 Hours,

## 13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

**Disposal instructions**Contents under pressure. Dispose of this material and its container at hazardous or

special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

### 14. Transport Information

#### **Department of Transportation (DOT) Requirements**

**Basic shipping requirements:** 

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions156, 306Packaging non bulk156, 306Packaging bulkNone

#### **IMDG**

**Basic shipping requirements:** 

**AEROSOLS** Proper shipping name

**Hazard class** 2.1 1950 **UN number** 

Additional information:

LTD QTY **Packaging exceptions** Labels required None



#### IATA

**Basic shipping requirements:** 

Proper shipping name Aerosols, flammable

**Hazard class** 2.1 **UN number** 1950

Additional information:

Packaging exceptions LTD QTY Labels required 2.1



# 15. Regulatory Information

**US** federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

2-Butoxyethanol 111-76-2 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3,

R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or

sulfonate, Chemical Category N230)

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

**CERCLA (Superfund) reportable quantity** 

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Nο

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely

hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region Inventory name On inventory (yes/no)\* China No

Inventory of Existing Chemical Substances in China (IECSC) European Inventory of New and Existing Chemicals (EINECS) Europe No European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan Nο Korea Existing Chemicals List (ECL) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

2-Butoxyethanol 111-76-2 Present 106-97-8 n-Butane Present

trade\_name MSDS US

### 16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 1 Flammability: 1

Physical hazard: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.

Prepared by

Regulatory Compliance